

Tactical Tracker 2600

The Tactical Tracker 2600 is a compact tracking antenna, designed to be modular, enabling resilient communications in any orbit, constellation, or band. Optimized for the modern warfighter, it provides secure, critical data connectivity. Its rapid deployment and proven reliability ensure command at the tactical edge in demanding operational environments.

Multi-Orbit, Multi-Band Performance

Supports GEO, MEO, LEO, HEO, and future constellations with RF options for S, C, X, Ku, and Ka-bands.

Rapid Deployment

From case to “on the air” in as little as 20 minutes with a user-friendly, tool-free assembly process.

Industry-Leading Retrace Speed

An advanced controller and drive system deliver an industry-leading retrace capability, enabling single-antenna NGSO operation without dropping modem encryption.

Control Interface

- Controller is embedded into pedestal
- OpenAMIP and closed loop mode compatible
- Enhanced GUI for ease of setup and operation
- Advanced software tracks the best signal available
- Support for TLE as well as CLI protocols

Rugged & Reliable

Designed for the rigorous duty cycle of LEO tracking and built to comply with rigorous DISA standards for secure communications at the edge.

Modular & Mission-Ready

Field-swappable RF packages and feeds allow for seamless adaptation to virtually any frequency band or mission set.

Precision Tracking

A high-precision carbon fiber reflector and sophisticated, time-tested pointing algorithms ensure superior tracking accuracy and full hemispheric coverage with no keyhole.

Options

- RF kits available: Ka, Ku, X, C, S Bands available
- BUC options with mounting kits available
- Anchoring kit options available
- Spare Parts kit available
- Custom packaging configurations available



Mechanical Specifications		Packaging Specifications (6 Cases)	
Drive	Motorized X over Y Positioner	Reflector Case	24 in x 45 in x 41 in - 176 lbs
Polarization	Circular Ka, X, Linear Ku	Leg/Strut Case	13 in x 66 in x 21 in - 120 lbs
Reflector	Segmented 8-Piece Carbon Fiber	Lower Positioner Case	18 in x 36 in x 20 in - 89.5 lbs
Retrace Speed	5 Degrees per second	Upper Positioner Case	18 in x 36 in x 20 in - 85.3 lbs
Power Supply	110/220 V 50/60 Hz	Pedestal/Controller Case	17 in x 23 in x 54in - 155 lbs
		RF Case <i>(Varies per configuration)</i>	13 in x 32 in 20 in - 69.4 lbs

Environmental Specifications		
Wind - Operational <i>(When anchored per specification)</i>	30 MPH gusting to 45 MPH	(48 KPH gusting to 72 KPH)
Wind - Survival <i>(When anchored per specification)</i>	60 MPH	(96 KPH)
Temperature Operational	-22° to 140° Fahrenheit	(-30° to 60° Celsius)
Temperature Survival	-40° to 158° Fahrenheit	(-40° to 70° Celsius)

RF / Electrical	Ka Band Military		Ka Band Commercial		Ku Band		X Band	
RF Parameters	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit
Frequency	20.2-21.2 GHz	30.0-31.0 GHz	17.7-20.2 GHz	27.5-30.0 GHz	10.7-12.75 GHz	13.75-14.5 GHz	7.25-7.75 GHz	7.9-8.4 GHz
Polarization	Circular Xpol	Circular Xpol	Circular Xpol	Circular Xpol	Linear Xpol	Linear Xpol	Circular Xpol	Circular Xpol
Gain @ Mid Band (dBi)	52.2 dBi	54.7 dBi	51.8 dBi	54.7 dBi	47.6 dBi	48.7 dBi	43.8 dBi	44.0 dBi
VSWR	1.3: 1 Typical	1.3: 1 Typical	1.3: 1 Typical	1.3: 1 Typical	1.3: 1 Typical	1.3: 1 Typical	1.3: 1 Typical	1.3: 1 Typical
Radiation Pattern Compliance	Mil-STD-188-164A	Mil-STD-188-164A	FCC 25.209, Mil-STD-188-164A	FCC 25.209, Mil-STD-188-164A	FCC 25.209, ITU-R S.580-6	FCC 25.209, ITU-R S.580-6	Mil-STD-188-164A	Mil-STD-188-164A
Power Handling Capability	NA	250 Watts	NA	250 Watts	NA	400 Watts	NA	500 Watts
G/T @ Mid-Band	29.5 dB/K	NA	29.2 dB/K	NA	27.3 dB/K	NA	23.9 dB/K	NA
Axial Ratio	1.5	1.0	1.5	1.0	NA	NA	1.2	2.0
Cross Pol Isolation	>22 dB Typical	>25 dB Typical	>22 dB Typical	>25 dB Typical	>30 dB	>30 dB	>23 dB Typical	>20 dB Typical
Feed Port Isolation	> 35 dB	> 80 dB	> 35 dB	> 80 dB	> 35 dB	> 80 dB	> 110 dB	> 110 dB

**All specs subject to change. All trademarks are the property of their respective owners. Information in this document is subject to change without notice.*

